The filling values and the correct operation of the product have been tested with a 60% dough hydration. The minimum dough weight achievable is approximately 1/4 of the capacity in kg (water + flour) for the 7, 10, 15, 17-liter versions and about 1/5 of the capacity for the 22, 33, 42, 53-liter versions.

Code	Model	Dimensions LxWxH cm						
P01IF01037	IFM7		$\longleftrightarrow$	25		50	$\bigcirc$	51
	Control		Capacità m	nax vasca (litri)		Capacità m	ax vasca (k	g)
	Manual		7			6		
	Dim. vasca (ø x H cm)						Weight Kg	1
	24x16						41	
	Total Power KW	Voltage V	Phases Ph			Frequency	Hz	
	0.30	230	1N+	Т		50		





Via Carnia 15, Z.I.P.R. 33078 San Vito al Tagliamento +39 0434 857000 (Pn)— Italia

info@pizzagroup.com www.pizzagroup.com



Code

P01IF01037

Model IFM7

#### **General Features**

Basin, lid, spiral, and dough breaker in stainless steel.	Single, double, or variable speed.	Available with removable tub or fixed head.	Constant dough temperature during processing.
Preselect the duration of your dough processing with the practical timer.	Models also available on wheels for maximum mobility and easy cleaning.	Ease of use for minimal space.	Available in multiple capacities, from 6 to 44 kg.





Code

P01IF01037

Model IFM7

## **Options**

#### SPIRAL MIXER WHEELS

WHEELS FOR MIXER, 2 WITH BRAKE, 2 WITHOUT BRAKE

Code



S66RU67001





The filling values and the correct operation of the product have been tested with a 60% dough hydration. The minimum dough weight achievable is approximately 1/4 of the capacity in kg (water + flour) for the 7, 10, 15, 17-liter versions and about 1/5 of the capacity for the 22, 33, 42, 53-liter versions.

Code	Model	Dimensions LxWxH cm						
P01IF01032	IFM10		$\longleftrightarrow$	27		54	$\bigcirc$	56
	Control		Capacità m	nax vasca (litri)	1	Capacità m	ax vasca (k	g)
	Manual		10			8		
	Dim. vasca (ø x H cm)						Weight Kg	
	26x20						48	
	Total Power KW	Voltage V	Phases Ph			Frequency	Hz	
	0.37	230	1N+	Т		50		





Via Carnia 15, Z.I.P.R. 33078 San Vito al Tagliamento +39 0434 857000 (Pn)— Italia

info@pizzagroup.com www.pizzagroup.com



Code

P01IF01032



#### **General Features**

Basin, lid, spiral, and dough breaker in stainless steel.	Single, double, or variable speed.	Available with removable tub or fixed head.	Constant dough temperature during processing.
Preselect the duration of your dough processing with the practical timer.	Models also available on wheels for maximum mobility and easy cleaning.	Ease of use for minimal space.	Available in multiple capacities, from 6 to 44 kg.





Code

P01IF01032

Model IFM10



#### SPIRAL MIXER WHEELS

WHEELS FOR MIXER, 2 WITH BRAKE, 2 WITHOUT BRAKE

Code



S66RU67001





The filling values and the correct operation of the product have been tested with a 60% dough hydration. The minimum dough weight achievable is approximately 1/4 of the capacity in kg (water + flour) for the 7, 10, 15, 17-liter versions and about 1/5 of the capacity for the 22, 33, 42, 53-liter versions.

Code	Model	Dimensions LxWxH cm						
P01IF01033	IFM15		$\longleftrightarrow$	32		59	$\bigcirc$	57
	Control		Capacità m	nax vasca (litri)		Capacità m	ax vasca (k	g)
	Manual		15			10		
	Dim. vasca (ø x H cm)						Weight Kg	
	30x21						50	
	Total Power KW	Voltage V	Phases Ph			Frequency	Hz	
	0.45	230	1N+	Т		50		





Via Carnia 15, Z.I.P.R. 33078 San Vito al Tagliamento +39 0434 857000 (Pn)— Italia

info@pizzagroup.com www.pizzagroup.com



Code

P01IF01033



#### **General Features**

Basin, lid, spiral, and dough breaker in stainless steel.	Single, double, or variable speed.	Available with removable tub or fixed head.	Constant dough temperature during processing.
Preselect the duration of your dough processing with the practical timer.	Models also available on wheels for maximum mobility and easy cleaning.	Ease of use for minimal space.	Available in multiple capacities, from 6 to 44 kg.





Code

P01IF01033

Model IFM15

## **Options**

#### SPIRAL MIXER WHEELS

WHEELS FOR MIXER, 2 WITH BRAKE, 2 WITHOUT BRAKE

Code



S66RU67001





The filling values and the correct operation of the product have been tested with a 60% dough hydration. The minimum dough weight achievable is approximately 1/4 of the capacity in kg (water + flour) for the 7, 10, 15, 17-liter versions and about 1/5 of the capacity for the 22, 33, 42, 53-liter versions.

Code	Model	Dimensior	ns LxWxH cm					
P01IF02034	IF17		$\longleftrightarrow$	35		66	<b>1</b>	63
	Control		Capacità r	max vasca (litr	i)	Capacità n	nax vasca (k	g)
	Manual		17			12		
	Dim. vasca (ø x H cm)						Weight Kg	9
	32x21						72	
	Total Power KW	Voltage V	Phases Ph	I		Frequency	Hz	
	0.75	400	3+T	-		50		





Via Carnia 15, Z.I.P.R. 33078 San Vito al Tagliamento +39 0434 857000 (Pn)— Italia

info@pizzagroup.com www.pizzagroup.com



Code

P01IF02034

Model IF17

#### **General Features**

Basin, lid, spiral, and dough breaker in stainless steel.	Single, double, or variable speed.	Available with removable tub or fixed head.	Constant dough temperature during processing.
Preselect the duration of your dough processing with the practical timer.	Models also available on wheels for maximum mobility and easy cleaning.	Ease of use for minimal space.	Available in multiple capacities, from 6 to 44 kg.





Code P01IF02034



#### **Options**

#### SPIRAL MIXER WHEELS

WHEELS FOR MIXER, 2 WITH BRAKE, 2 WITHOUT BRAKE

Code



S66RU67001



Via Carnia 15, Z.I.P.R. 33078 San Vito al Tagliamento +39 0434 857000 (Pn)— Italia

info@pizzagroup.com www.pizzagroup.com



The filling values and the correct operation of the product have been tested with a 60% dough hydration. The minimum dough weight achievable is approximately 1/4 of the capacity in kg (water + flour) for the 7, 10, 15, 17-liter versions and about 1/5 of the capacity for the 22, 33, 42, 53-liter versions.

Code	Model		Dimension	s LxWxH cm				
P01IF01034	IFM17		$\longleftrightarrow$	35		66	$\bigcirc$	63
	Control		Capacità m	nax vasca (litri)	)	Capacità m	nax vasca (k	g)
	Manual		17			12		
	Dim. vasca (ø x H cm)						Weight Kg	J
	32x21						79	
	Total Power KW	Voltage V	Phases Ph			Frequency	Hz	
	0.90	230	1N+	Т		50		





Via Carnia 15, Z.I.P.R. 33078 San Vito al Tagliamento +39 0434 857000 (Pn)— Italia

info@pizzagroup.com www.pizzagroup.com



Code

P01IF01034

Model IFM17

#### **General Features**

Basin, lid, spiral, and dough breaker in stainless steel.	Single, double, or variable speed.	Available with removable tub or fixed head.	Constant dough temperature during processing.
Preselect the duration of your dough processing with the practical timer.	Models also available on wheels for maximum mobility and easy cleaning.	Ease of use for minimal space.	Available in multiple capacities, from 6 to 44 kg.





Code

P01IF01034

Model IFM17

## **Options**

#### SPIRAL MIXER WHEELS

WHEELS FOR MIXER, 2 WITH BRAKE, 2 WITHOUT BRAKE

Code



S66RU67001





The filling values and the correct operation of the product have been tested with a 60% dough hydration. The minimum dough weight achievable is approximately 1/4 of the capacity in kg (water + flour) for the 7, 10, 15, 17-liter versions and about 1/5 of the capacity for the 22, 33, 42, 53-liter versions.

Code	Model	Dimension	s LxWxH cm					
P01IF02035	IF22		$\longleftrightarrow$	40		69	$\bigcirc$	63
	Control		Capacità m	nax vasca (litri)	)	Capacità m	ax vasca (k	g)
	Manual		22			18		
	Dim. vasca (ø x H cm)						Weight Kg	
	36x21						75	
	Total Power KW	Voltage V	Phases Ph			Frequency	Hz	
	0.75	400	3+T			50		





Via Carnia 15, Z.I.P.R. 33078 San Vito al Tagliamento +39 0434 857000 (Pn)— Italia

info@pizzagroup.com www.pizzagroup.com



Code

P01IF02035

Model IF22

#### **General Features**

Basin, lid, spiral, and dough breaker in stainless steel.	Single, double, or variable speed.	Available with removable tub or fixed head.	Constant dough temperature during processing.
Preselect the duration of your dough processing with the practical timer.	Models also available on wheels for maximum mobility and easy cleaning.	Ease of use for minimal space.	Available in multiple capacities, from 6 to 44 kg.





Code

P01IF02035

Model IF22



#### SPIRAL MIXER WHEELS

WHEELS FOR MIXER, 2 WITH BRAKE, 2 WITHOUT BRAKE

Code



S66RU67001





The filling values and the correct operation of the product have been tested with a 60% dough hydration. The minimum dough weight achievable is approximately 1/4 of the capacity in kg (water + flour) for the 7, 10, 15, 17-liter versions and about 1/5 of the capacity for the 22, 33, 42, 53-liter versions.

Code	Model	Dimensions LxWxH cm	
P01IF04027	IF22 2V	$\leftrightarrow$ 40 $arsigma$	69  ↓ 63
	Control	Capacità max vasca (litri)	Capacità max vasca (kg)
	Manual	22	18
	Dim. vasca (ø x H cm)		Weight Kg
	36x21		73
	Total Power KW Voltage V	Phases Ph	Frequency Hz
	0.37/0. 400	3+T	50





Via Carnia 15, Z.I.P.R. 33078 San Vito al Tagliamento +39 0434 857000 (Pn)— Italia

info@pizzagroup.com www.pizzagroup.com



Code

P01IF04027

Model IF22 2V

#### **General Features**

Basin, lid, spiral, and dough breaker in stainless steel.	Single, double, or variable speed.	Available with removable tub or fixed head.	Constant dough temperature during processing.
Preselect the duration of your dough processing with the practical timer.	Models also available on wheels for maximum mobility and easy cleaning.	Ease of use for minimal space.	Available in multiple capacities, from 6 to 44 kg.





Code

P01IF04027

Model IF22 2V

## **Options**

#### SPIRAL MIXER WHEELS

WHEELS FOR MIXER, 2 WITH BRAKE, 2 WITHOUT BRAKE

Code



S66RU67001





The filling values and the correct operation of the product have been tested with a 60% dough hydration. The minimum dough weight achievable is approximately 1/4 of the capacity in kg (water + flour) for the 7, 10, 15, 17-liter versions and about 1/5 of the capacity for the 22, 33, 42, 53-liter versions.

Code	Model	Dimension	s LxWxH cm					
P01IF03021	IF22 VS		$\longleftrightarrow$	40		69	$\bigcirc$	63
	Control		Capacità n	nax vasca (litri	)	Capacità m	nax vasca (k	g)
	Manual		22			18		
	Dim. vasca (ø x H cm)						Weight Kg	1
	36x21						76	
	Total Power KW	Voltage V	Phases Ph			Frequency	Hz	
	0.75	230	1N+	Т		50		





Via Carnia 15, Z.I.P.R. 33078 San Vito al Tagliamento +39 0434 857000 (Pn)— Italia

info@pizzagroup.com www.pizzagroup.com



Code

P01IF03021



#### **General Features**

Basin, lid, spiral, and dough breaker in stainless steel.	Single, double, or variable speed.	Available with removable tub or fixed head.	Constant dough temperature during processing.
Preselect the duration of your dough processing with the practical timer.	Models also available on wheels for maximum mobility and easy cleaning.	Ease of use for minimal space.	Available in multiple capacities, from 6 to 44 kg.





Code

P01IF03021

Model IF22 VS

## **Options**

#### SPIRAL MIXER WHEELS

WHEELS FOR MIXER, 2 WITH BRAKE, 2 WITHOUT BRAKE

Code



S66RU67001





The filling values and the correct operation of the product have been tested with a 60% dough hydration. The minimum dough weight achievable is approximately 1/4 of the capacity in kg (water + flour) for the 7, 10, 15, 17-liter versions and about 1/5 of the capacity for the 22, 33, 42, 53-liter versions.

Code	Model	Dimension	s LxWxH cm					
P01IF01035	IFM22		$\longleftrightarrow$	40		69	$\bigcirc$	63
	Control		Capacità m	nax vasca (litrij	)	Capacità m	nax vasca (k	g)
	Manual		22			18		
	Dim. vasca (ø x H cm)					-	Weight Kg	9
	36x21						82	
	Total Power KW	Voltage V	Phases Ph			Frequency	Hz	
	0.90	230	3+T			50		





Via Carnia 15, Z.I.P.R. 33078 San Vito al Tagliamento +39 0434 857000 (Pn)— Italia

info@pizzagroup.com www.pizzagroup.com



Code

P01IF01035

Model IFM22

#### **General Features**

Basin, lid, spiral, and dough breaker in stainless steel.	Single, double, or variable speed.	Available with removable tub or fixed head.	Constant dough temperature during processing.
Preselect the duration of your dough processing with the practical timer.	Models also available on wheels for maximum mobility and easy cleaning.	Ease of use for minimal space.	Available in multiple capacities, from 6 to 44 kg.





Code

P01IF01035

Model IFM22

## **Options**

#### SPIRAL MIXER WHEELS

WHEELS FOR MIXER, 2 WITH BRAKE, 2 WITHOUT BRAKE

Code



S66RU67001





The filling values and the correct operation of the product have been tested with a 60% dough hydration. The minimum dough weight achievable is approximately 1/4 of the capacity in kg (water + flour) for the 7, 10, 15, 17-liter versions and about 1/5 of the capacity for the 22, 33, 42, 53-liter versions.

Code	Model	Dimensions LxWxH cm						
P01IF02036	IF33		$\longleftrightarrow$	44		83	$\uparrow$	72
	Control		Capacità m	nax vasca (litri)	)	Capacità m	ax vasca (k	g)
	Manual		33			25		
	Dim. vasca (ø x H cm)						Weight Kg	1
	40x26						104	
	Total Power KW	Voltage V	Phases Ph			Frequency	Hz	
	1.50	400	3+T			50		





Via Carnia 15, Z.I.P.R. 33078 San Vito al Tagliamento +39 0434 857000 (Pn)— Italia

info@pizzagroup.com www.pizzagroup.com



Code

P01IF02036

Model IF33

#### **General Features**

Basin, lid, spiral, and dough breaker in stainless steel.	Single, double, or variable speed.	Available with removable tub or fixed head.	Constant dough temperature during processing.
Preselect the duration of your dough processing with the practical timer.	Models also available on wheels for maximum mobility and easy cleaning.	Ease of use for minimal space.	Available in multiple capacities, from 6 to 44 kg.





Code

P01IF02036

Model IF33



#### SPIRAL MIXER WHEELS

WHEELS FOR MIXER, 2 WITH BRAKE, 2 WITHOUT BRAKE

Code



S66RU67001



Via Carnia 15, Z.I.P.R. 33078 San Vito al Tagliamento +39 0434 857000 (Pn)— Italia

info@pizzagroup.com www.pizzagroup.com



The filling values and the correct operation of the product have been tested with a 60% dough hydration. The minimum dough weight achievable is approximately 1/4 of the capacity in kg (water + flour) for the 7, 10, 15, 17-liter versions and about 1/5 of the capacity for the 22, 33, 42, 53-liter versions.

Code	Model	Dimensions LxWxH cm	
P01IF04028	IF33 2V	$\leftrightarrow$ 44 $\bigvee$	83 1 72
	Control	Capacità max vasca (litri)	Capacità max vasca (kg)
	Manual	33	25
	Dim. vasca (ø x H cm)		Weight Kg
	40x26		<u> </u>
	Total Power KW Voltage V	Phases Ph	Frequency Hz
	0.75/1.1 400	1N+T	50





Via Carnia 15, Z.I.P.R. 33078 San Vito al Tagliamento +39 0434 857000 (Pn)— Italia

info@pizzagroup.com www.pizzagroup.com



Code

P01IF04028

Model IF33 2V

#### **General Features**

Basin, lid, spiral, and dough breaker in stainless steel.	Single, double, or variable speed.	Available with removable tub or fixed head.	Constant dough temperature during processing.
Preselect the duration of your dough processing with the practical timer.	Models also available on wheels for maximum mobility and easy cleaning.	Ease of use for minimal space.	Available in multiple capacities, from 6 to 44 kg.





Code

P01IF04028

Model IF33 2V



#### SPIRAL MIXER WHEELS

WHEELS FOR MIXER, 2 WITH BRAKE, 2 WITHOUT BRAKE

Code



S66RU67001



Via Carnia 15, Z.I.P.R. 33078 San Vito al Tagliamento +39 0434 857000 (Pn)— Italia

info@pizzagroup.com www.pizzagroup.com



The filling values and the correct operation of the product have been tested with a 60% dough hydration. The minimum dough weight achievable is approximately 1/4 of the capacity in kg (water + flour) for the 7, 10, 15, 17-liter versions and about 1/5 of the capacity for the 22, 33, 42, 53-liter versions.

Code	Model	Dimensions LxWxH cm						
P01IF03022	IF33 VS		$\longleftrightarrow$	44		83	$\uparrow$	72
	Control		Capacità m	ax vasca (litri)		Capacità m	ax vasca (k	g)
	Manual		33			25		
	Dim. vasca (ø x H cm)						Weight Kg	
	40x26						106	
	Total Power KW	Voltage V	Phases Ph			Frequency	Hz	
	1.50	230	1N+	Т		50		





Via Carnia 15, Z.I.P.R. 33078 San Vito al Tagliamento +39 0434 857000 (Pn)— Italia

info@pizzagroup.com www.pizzagroup.com



Code

P01IF03022



#### **General Features**

Basin, lid, spiral, and dough breaker in stainless steel.	Single, double, or variable speed.	Available with removable tub or fixed head.	Constant dough temperature during processing.
Preselect the duration of your dough processing with the practical timer.	Models also available on wheels for maximum mobility and easy cleaning.	Ease of use for minimal space.	Available in multiple capacities, from 6 to 44 kg.



Via Carnia 15, Z.I.P.R. 33078 San Vito al Tagliamento +39 0434 857000 (Pn)— Italia

info@pizzagroup.com www.pizzagroup.com



Code

P01IF03022

Model IF33 VS

## **Options**

#### SPIRAL MIXER WHEELS

WHEELS FOR MIXER, 2 WITH BRAKE, 2 WITHOUT BRAKE

Code



S66RU67001





The filling values and the correct operation of the product have been tested with a 60% dough hydration. The minimum dough weight achievable is approximately 1/4 of the capacity in kg (water + flour) for the 7, 10, 15, 17-liter versions and about 1/5 of the capacity for the 22, 33, 42, 53-liter versions.

Code	Model	Dimensions LxWxH cm						
P01IF01036	IFM33		$\longleftrightarrow$	44		83	$\bigcirc$	72
	Control		Capacità m	nax vasca (litri)	)	Capacità m	nax vasca (k	g)
	Manual		33			25		
	Dim. vasca (ø x H cm)						Weight Kg	1
	40x26						110	
	Total Power KW	Voltage V	Phases Ph			Frequency	Hz	
	1.30	230	3+T			50		





Via Carnia 15, Z.I.P.R. 33078 San Vito al Tagliamento +39 0434 857000 (Pn)— Italia

info@pizzagroup.com www.pizzagroup.com



Code

P01IF01036

Model IFM33

#### **General Features**

Basin, lid, spiral, and dough breaker in stainless steel.	Single, double, or variable speed.	Available with removable tub or fixed head.	Constant dough temperature during processing.
Preselect the duration of your dough processing with the practical timer.	Models also available on wheels for maximum mobility and easy cleaning.	Ease of use for minimal space.	Available in multiple capacities, from 6 to 44 kg.



Via Carnia 15, Z.I.P.R. 33078 San Vito al Tagliamento +39 0434 857000 (Pn)— Italia



Code

P01IF01036

Model IFM33

## **Options**

#### SPIRAL MIXER WHEELS

WHEELS FOR MIXER, 2 WITH BRAKE, 2 WITHOUT BRAKE

Code







The filling values and the correct operation of the product have been tested with a 60% dough hydration. The minimum dough weight achievable is approximately 1/4 of the capacity in kg (water + flour) for the 7, 10, 15, 17-liter versions and about 1/5 of the capacity for the 22, 33, 42, 53-liter versions.

Code	Model		Dimension	s LxWxH cm			
P01IF02037	IF42		$\longleftrightarrow$	47	85	$\uparrow$	72
	Control		Capacità m	nax vasca (litri)	Capacità m	nax vasca (k	g)
	Manual		42		38		
	Dim. vasca (ø x H cm)					Weight Kg	
	45x26					107	
	Total Power KW	Voltage V	Phases Ph		Frequency	Hz	
	1.50	400	3+T		50		





Via Carnia 15, Z.I.P.R. 33078 San Vito al Tagliamento +39 0434 857000 (Pn)— Italia

info@pizzagroup.com www.pizzagroup.com



Code

P01IF02037

Model IF42

#### **General Features**

Basin, lid, spiral, and dough breaker in stainless steel.	Single, double, or variable speed.	Available with removable tub or fixed head.	Constant dough temperature during processing.
Preselect the duration of your dough processing with the practical timer.	Models also available on wheels for maximum mobility and easy cleaning.	Ease of use for minimal space.	Available in multiple capacities, from 6 to 44 kg.





Code

P01IF02037

Model IF42

## **Options**

#### SPIRAL MIXER WHEELS

WHEELS FOR MIXER, 2 WITH BRAKE, 2 WITHOUT BRAKE

Code







The filling values and the correct operation of the product have been tested with a 60% dough hydration. The minimum dough weight achievable is approximately 1/4 of the capacity in kg (water + flour) for the 7, 10, 15, 17-liter versions and about 1/5 of the capacity for the 22, 33, 42, 53-liter versions.

Code	Model	Dimensions LxWxH cm	
P01IF04029	IF42 2V	↔ 47 1⁄7	85 1 72
	Control	Capacità max vasca (litri)	Capacità max vasca (kg)
	Manual	42	38
	Dim. vasca (ø x H cm)		Weight Kg
	45x26		<u> </u>
	Total Power KW Voltage V	Phases Ph	Frequency Hz
	1.50/2.0 400	1N+T	50





Via Carnia 15, Z.I.P.R. 33078 San Vito al Tagliamento +39 0434 857000 (Pn)— Italia

info@pizzagroup.com www.pizzagroup.com



Code

P01IF04029

Model IF42 2V

#### **General Features**

Basin, lid, spiral, and dough breaker in stainless steel.	Single, double, or variable speed.	Available with removable tub or fixed head.	Constant dough temperature during processing.
Preselect the duration of your dough processing with the practical timer.	Models also available on wheels for maximum mobility and easy cleaning.	Ease of use for minimal space.	Available in multiple capacities, from 6 to 44 kg.



Via Carnia 15, Z.I.P.R. 33078 San Vito al Tagliamento +39 0434 857000 (Pn)— Italia

info@pizzagroup.com www.pizzagroup.com



Code

P01IF04029

Model IF42 2V

## **Options**

#### SPIRAL MIXER WHEELS

WHEELS FOR MIXER, 2 WITH BRAKE, 2 WITHOUT BRAKE

Code



S66RU67001



Via Carnia 15, Z.I.P.R. 33078 San Vito al Tagliamento +39 0434 857000 (Pn)— Italia

info@pizzagroup.com www.pizzagroup.com



The filling values and the correct operation of the product have been tested with a 60% dough hydration. The minimum dough weight achievable is approximately 1/4 of the capacity in kg (water + flour) for the 7, 10, 15, 17-liter versions and about 1/5 of the capacity for the 22, 33, 42, 53-liter versions.

Code	Model	Dimensions LxWxH cm						
P01IF03023	IF42 VS		$\longleftrightarrow$	47		85	$\uparrow$	72
	Control		Capacità m	nax vasca (litri)		Capacità m	ax vasca (k	g)
	Manual		42			38		
	Dim. vasca (ø x H cm)						Weight Kg	
	45x26						109	
	Total Power KW	Voltage V	Phases Ph			Frequency	Hz	
	1.50	230	1N+	Т		50		





Via Carnia 15, Z.I.P.R. 33078 San Vito al Tagliamento +39 0434 857000 (Pn)— Italia

info@pizzagroup.com www.pizzagroup.com



Code

P01IF03023



#### **General Features**

Basin, lid, spiral, and dough breaker in stainless steel.	Single, double, or variable speed.	Available with removable tub or fixed head.	Constant dough temperature during processing.
Preselect the duration of your dough processing with the practical timer.	Models also available on wheels for maximum mobility and easy cleaning.	Ease of use for minimal space.	Available in multiple capacities, from 6 to 44 kg.



Via Carnia 15, Z.I.P.R. 33078 San Vito al Tagliamento +39 0434 857000 (Pn)— Italia

info@pizzagroup.com www.pizzagroup.com



Code

P01IF03023

Model IF42 VS

## **Options**

#### SPIRAL MIXER WHEELS

WHEELS FOR MIXER, 2 WITH BRAKE, 2 WITHOUT BRAKE

Code







The filling values and the correct operation of the product have been tested with a 60% dough hydration. The minimum dough weight achievable is approximately 1/4 of the capacity in kg (water + flour) for the 7, 10, 15, 17-liter versions and about 1/5 of the capacity for the 22, 33, 42, 53-liter versions.

Code	Model		Dimension	s LxWxH cm			
P01IF02038	IF53		$\longleftrightarrow$	53	86	$\bigcirc$	72
	Control		Capacità m	nax vasca (litri)	Capacità m	nax vasca (k	g)
	Manual		53		44		
	Dim. vasca (ø x H cm)					Weight Kg	
	50x27					110	
	Total Power KW	Voltage V	Phases Ph		Frequency	Hz	
	1.50	400	3+T		50		





Via Carnia 15, Z.I.P.R. 33078 San Vito al Tagliamento +39 0434 857000 (Pn)— Italia

info@pizzagroup.com www.pizzagroup.com



Code

P01IF02038



#### **General Features**

Basin, lid, spiral, and dough breaker in stainless steel.	Single, double, or variable speed.	Available with removable tub or fixed head.	Constant dough temperature during processing.
Preselect the duration of your dough processing with the practical timer.	Models also available on wheels for maximum mobility and easy cleaning.	Ease of use for minimal space.	Available in multiple capacities, from 6 to 44 kg.



Via Carnia 15, Z.I.P.R. 33078 San Vito al Tagliamento +39 0434 857000 (Pn)— Italia



Code

P01IF02038

Model IF53



#### SPIRAL MIXER WHEELS

WHEELS FOR MIXER, 2 WITH BRAKE, 2 WITHOUT BRAKE

Code



S66RU67001



Via Carnia 15, Z.I.P.R. 33078 San Vito al Tagliamento +39 0434 857000 (Pn)— Italia

info@pizzagroup.com www.pizzagroup.com



The filling values and the correct operation of the product have been tested with a 60% dough hydration. The minimum dough weight achievable is approximately 1/4 of the capacity in kg (water + flour) for the 7, 10, 15, 17-liter versions and about 1/5 of the capacity for the 22, 33, 42, 53-liter versions.

Code	Model	Dimensions LxWxH cm	
P011F04030	IF53 2V	$\leftrightarrow$ 53 $\checkmark$	86 1 72
	Control	Capacità max vasca (litri)	Capacità max vasca (kg)
	Manual	53	44
	Dim. vasca (ø x H cm)	· · · ·	Weight Kg
	50x27		<u>(</u> 109
	Total Power KW Voltage V	Phases Ph	Frequency Hz
	1.50/2.0 400	3+T	50





Via Carnia 15, Z.I.P.R. 33078 San Vito al Tagliamento +39 0434 857000 (Pn)— Italia

info@pizzagroup.com www.pizzagroup.com



Code

P01IF04030

Model IF53 2V

#### **General Features**

Basin, lid, spiral, and dough breaker in stainless steel.	Single, double, or variable speed.	Available with removable tub or fixed head.	Constant dough temperature during processing.
Preselect the duration of your dough processing with the practical timer.	Models also available on wheels for maximum mobility and easy cleaning.	Ease of use for minimal space.	Available in multiple capacities, from 6 to 44 kg.



Via Carnia 15, Z.I.P.R. 33078 San Vito al Tagliamento +39 0434 857000 (Pn)— Italia

info@pizzagroup.com www.pizzagroup.com



Code

P01IF04030

Model IF53 2V

## **Options**

#### SPIRAL MIXER WHEELS

WHEELS FOR MIXER, 2 WITH BRAKE, 2 WITHOUT BRAKE

Code







The filling values and the correct operation of the product have been tested with a 60% dough hydration. The minimum dough weight achievable is approximately 1/4 of the capacity in kg (water + flour) for the 7, 10, 15, 17-liter versions and about 1/5 of the capacity for the 22, 33, 42, 53-liter versions.

Code	Model	Dimensions LxWxH cm						
P01IF03024	IF53 VS		$\longleftrightarrow$	53		86	$\uparrow$	72
	Control		Capacità m	nax vasca (litri)		Capacità m	nax vasca (ke	g)
	Manual		53			44		
	Dim. vasca (ø x H cm)						Weight Kg	
	50x27						112	
	Total Power KW	Voltage V	Phases Ph			Frequency	Hz	
	1.50	230	1N+	Т		50		





Via Carnia 15, Z.I.P.R. 33078 San Vito al Tagliamento +39 0434 857000 (Pn)— Italia

info@pizzagroup.com www.pizzagroup.com



Code

P01IF03024



#### **General Features**

Basin, lid, spiral, and dough breaker in stainless steel.	Single, double, or variable speed.	Available with removable tub or fixed head.	Constant dough temperature during processing.
Preselect the duration of your dough processing with the practical timer.	Models also available on wheels for maximum mobility and easy cleaning.	Ease of use for minimal space.	Available in multiple capacities, from 6 to 44 kg.



Via Carnia 15, Z.I.P.R. 33078 San Vito al Tagliamento +39 0434 857000 (Pn)— Italia

info@pizzagroup.com www.pizzagroup.com



Code

P01IF03024

Model IF53 VS

## **Options**

#### SPIRAL MIXER WHEELS

WHEELS FOR MIXER, 2 WITH BRAKE, 2 WITHOUT BRAKE

Code





